


HD180DK-4

Heavy Duty Ride-on Industrial Sweeper

PRESTART & OPERATION CHECKLIST



STEP 1
Read your Daily Operations Manual



STEP
Ensure clean path is free of strapping & large debris



STEP
Visually check over machine. Ensure radiator is clean and free from debris




STEP
Visually check radiator overflow tank has sufficient coolant. Top up if necessary




STEP
Turn key to ON position and depress accelerator. Move throttle to maximum RPM



STEP 1
Ensure hopper is completely down & secure



STEP
Activate main broom



STEP
Open hopper door




STEP
Start fan. Fan MUST be running while sweeping



STEP
Depress accelerator pedal to move and control speed


DAILY MAINTENANCE




STEP 1
Raise main broom to home position



STEP 2
Close hopper door flap




STEP 3
Activate filter shaker for 30 seconds



STEP 4
Raise hopper to maximum height



STEP 5
Position hopper over waste receptacle




STEP 6
Open hopper door




STEP 7
Reverse by depressing bottom of foot pedal



STEP 8
Ensure broom is free from strapping



STEP 9
Lower waste hopper



STEP 10
Refuel with approved diesel and replace cap



STEP 11
Park in designated area. Apply hand break



STEP 12
Report any damage

COMMON CONSUMABLES

PART NUMBER	DESCRIPTION
3007761	Main Broom PPL 1.2
3004330_A	Side Broom



Safe to operate machine



DO NOT operate machine