DAILY CHECKLIST

HDC170

Heavy Duty Combination Sweeper Scrubber

OPERATOR NAME		**DATE**	
MACHINE HOURS			

1. Operator is trained, has read the operator manual, and is wearing required PPE. ☐
2. Inspect the work area. Remove wire, tape, string, timber and large debris; identify slopes, traffic and other hazards. ☐
3. Walk around machine and check for fluid leaks, loose or damaged components, tyres and bumper wheels.
4. Check battery charge on the display. Recharge if required. ☐
5. Start machine and check display for alarms. Confirm emergency stop is released and electric brake is engaged. ☐
6. Test steering, service brake, horn, reverse alarm, headlights and safety lights, if fitted. ☐
7. Check solution level and detergent. Use approved low-foam scrubber detergent only; fill with clean water between 10°C and 50°C. ☐
8. Confirm recovery tank and debris hopper are empty and drain caps, lids and inspection doors are secure. ☐
9. Inspect squeegee, vacuum hose, brushes, side brushes and splash guards. Clean and confirm no excessive wear or damage. ☐
10. Check collection tray, wave protection tray, water filter and debris-hopper vacuum filter are clean. ☐
11. During the first metres, confirm correct solution flow, sweeping performance and a dry, streak-free floor. ☐
12. After use, set machine to TRANSFER mode and park in the designated maintenance area on a flat surface. ☐
13. Empty and rinse recovery tank and solution tank. Empty and clean the debris hopper. ☐
14. Clean squeegee and vacuum hoses; collection and wave trays; brushes, side brushes, splash guards and hopper vacuum filter. ☐
15. Return all controls to OFF, close the solution tap, secure lids/doors, charge battery as required and park safely. ☐

DEFECTS / DAMAGE FOUND:

Do not operate with a safety-critical fault or persistent alarm. Isolate the machine and report it to your supervisor or Conquest Service.

1800 100 150
parts@conquesteg.com
service@conquesteg.com

CONQUEST